

# > TABLA DESALIDA DE CABLES

TABLA DE SALIDA DE CABLES								
FASES	MODELO	H.P.	VOLTS	Hz		CABLE	AREA	AMPERES
					AMP.			
3	OR 25	2.5	220	60	8.2	10	5.2 6	31
3	OR 25	2.5	440	60	4.0	10	5.2 6	31
3	OR 30	3	220	60	8.2	10	5.2 6	31
3	OR 30	3	440	60	4.0	10	5.2 6	31
3	OR 40	4	220	60	12.5	10	5.2 6	31
3	OR 40	4	440	60	6.2	10	5.2 6	31
3	OR 50	5	220	60	15.4	10	5.2 6	31
3	OR 50	5	440	60	7.7	10	5.2 6	31
3	OR 75	8	220	60	22.4	10	5.2 6	31
3	OR 75	8	440	60	11.2	10	5.2 6	31
3	OR 10 0	10	220	60	28.5	10	5.2 6	31
3	OR 10 0	10	440	60	14.2	10	5.2 6	31
3	OR 13 0	13	220	60	36.0	8	8.3 5	50
3	OR 13 0	13	440	60	18.1	10	5.2 6	31
3	OR 16 0	16	220	60	44.0	6	13.3	70
3	OR 16 0	16	440	60	22.0	8	8.3 5	50
3	OR 20 0	20	220	60	55.0	4	21.15	90
3	OR 20 0	20	440	60	27.0	8	8.3 5	50
3	OR 25 0	25	220	60	68.0	4	21.15	90
3	OR 25 0	25	440	60	34.0	8	8.3 5	50
3	ORG 16 0	16	220	60	44.0	6	13.3	70
3	ORG 16 0	16	440	60	22.0	8	8.3 5	50
3	ORG 20 0	20	220	60	55.0	4	21.15	90
3	ORG 20 0	20	440	60	27.0	8	8.3 5	50
3	ORG 25 0	25	220	60	68.0	4	21.15	90
3	ORG 25 0	25	440	60	34.0	8	8.3 5	50
3	ORG 30 0	30	220	60	80.0	2	33.63	120
3	ORG 30 0	30	440	60	40.0	6	13.3	70
3	ORG 35 0	35	220	60	94.0	2	33.63	120
3	ORG 35 0	35	440	60	47.0	6	13.3	70
3	ORG 40 0	40	220	60	104.0	0	53.48	160
3	ORG 40 0	40	440	60	52.0	4	21.15	90
3	ORG 50 0	50	220	60	130.0	0	53.48	160
3	ORG 50 0	50	440	60	65.0	4	21.15	90
3	ORG 75 0	75	220	60	192.0	0	53.48	160
3	ORG 75 0	75	440	60	96.0	2	33.63	120
3	ME 400	40	220	60	104.0	0	53.48	160
3	ME 400	40	440	60	52.0	4	21.15	90
3	ME 500	50	220	60	130.0	0	53.48	160
3	ME 500	50	440	60	65.0	4	21.15	90
3	ME 750	75	220	60	192.0	0	53.48	160
3	ME 750	75	440	60	96.0	2	33.63	120
3	ME 1000	100	220	60	250.0	2 / 2	33.63	120
3	ME 1000	100	440	60	125.0	0	53.48	160
3	ME 1250	125	440	60	125.0	0	53.48	160
3	ME 1500	150	440	60	185.0	2 / 0	67.43	180
3	PT 12 50	125	440	60	154.0	0	53.48	160
3	PT 15 00	150	440	60	185.0	2 / 2	33.63	120
3	PT 20 00	200	440	60	255.0	2 / 0	67.43	180
3	PT 30 00	300	440	60	390.0	00 / 00	67.43	180